INSTRUMENTATION & CONTROL

Filtration Controller Set

G75-DFC-DC | Baccara Filtration Controller Set (DFC)



- Filtration backwash controller 1-3 stations
- Backwash by DP or time interval
- The assembly includes controller and differential pressure sensor
- Mounting bracket optional

Technical Data

leon nour bata	
Controller Set Supplied with	DFC controller, suitable for DC only, and one analog sensor
Mechanical	 Operating temperature : -10°C to 60°C Outdoor UV protection Front panel cover protection "H" proof pressure : 14 bar (203 PSI) "H" pressure must be ≥ "L" pressure.
Electrical	DC units are powered by single 9V alkaline battery; use best quality to ensure at least one year's autonomous operation. • Back-up memory • Low battery warning • Power saving LCD
Mounting	 Pressure ports 1/8" BSP/NPT (male) High pressure port is marked by the letter "H" on the housing Connect high pressure before low pressure Disconnect low pressure before high pressure Controller : Directly on a 28mm diameter solenoid in horizontal or vertical position with adaptor Wall mounting with four screws Accessories provided Sensor : 2" (52 mm diameter)
Software	See 'Programming key features' table
Options	Option to change default factory settings
Standard protection class	IP66 Dust and watertight
Solenoid	G75-A, GALIT Latch 4 Ω , G75-A3P 1 Ω

Programming key features

-	_	-	
Manual operat	tion		
Valve ON time			
Maximum time	e interv	al between	washes
Valve selection	n		

How to Order

G75-DFC-DC	ТҮРЕ		-	MOUNTING BRACKET	
	3 Valves	0		without	0
	3 Valves + 1 Main Valve	1		with	1

Example : G75-DFC-DC-1-1

GEVA 75 DFC-DC, 3 Valves + 1 Main valve, with mounting bracket

G75-DFC-DC - 1 - 1

* To order controllers manufactured according to your specific requirements, please contact our technical sales department.

