

ELECTRIC/HYDRAULIC VALVES | GEM & G75


G75-S | 3 Way Integral solenoid pilot control 3/4" - 2" NC




Upstream pilot control



External pilot control



Upstream pilot control



External pilot control

Technical Data

Solenoid	Supplied with 3W NO 1.2mm G75 operator
Assembly	Upstream pilot control valve is supplied with finger filter and accessories

• For technical information, refer to G75-S | Electric 3/4" - 2" 2 Way NC

Coil resistance vs input voltage range

Resistance [Ω]	Suitable input voltage range [V]
4	6 - 9
9	12 - 14
12	14 - 16
23	18 - 21

How to Order

G75-S	PORT	FUNCTION	MANUAL OVERRIDE	FLOW CONTROL	VOLTAGE ⁽³⁾	WIRES					
3/4" BSPT	50	External pilot	4	None	0	with	5	24V AC	1	two	null
3/4" NPT	51	Upstream pilot	4H	Plastic	1	without ⁽¹⁾	6	24V AC w/out Diode	1R	three ⁽²⁾	a
1" BSPT	60			Handle ⁽²⁾	2			12 V AC	3		
1" NPT	61							12 V DC	4		
1-1/2" BSPT	70							24V DC	5		
1-1/2" NPT	71							23 Ω	6		
2" BSPT	80							4 Ω	B		
2" NPT	81							9 Ω	C		
								12 Ω	D		

Example : G75-S-704151

G75 1-1/2" BSPT, external pilot, plastic manual override, with flow control, 24V AC, two wires

G75-S - 70 4 1 5 1

(1) For 3/4", 1" valves only

(2) For Latch only

(3) For Latch : Refer to coil resistance vs input voltage table

* To order valves manufactured according to your specific requirements, please contact our technical sales department