


PROCESS VALVES

Diaphragm | Plastic

G75-Z | Hydraulic zero differential pressure 3/4" - 2" 2 Way NO





1" | NO without flow control



Flow direction →

Dimensions

Size	A	B	C
3/4"	77	110	81
1"	84	110	81
1-1/2"	98	160	127
2"	98	170	127



Technical Data

Ports size	3/4", 1", 1-1/2", 2" BSPT & NPT
Pressure range	Line: 0-6 bar Pilot: 1.5 bar above line pressure
Temperature range	Fluid : 5°C to 50°C (no freezing)
Materials in contact with media	Main Valve: Reinforced Nylon Diaphragm: NR Seals: Buna-N Spring: Stainless Steel AISI 300 series

• For overall dimensions, refer to G75-S | Hydraulic 3/4" - 2" 2 Way

How to Order

G75-Z	-	PORT	FUNCTION	FLOW CONTROL		
		3/4" BSPT	50	2W NO 2	with	5
		3/4" NPT	51		without ⁽¹⁾	6
		1" BSPT	60			
		1" NPT	61			
		1-1/2" BSPT	70			
		1-1/2" NPT	71			
		2" BSPT	80			
		2" NPT	81			

Example : G75-Z-6025

G75 inline hydraulic valve, 1" BSPT, 2W NO with flow control

G75-Z	-	60	-	2	-	5
-------	---	----	---	---	---	---

(1) 3/4", 1" valves only

* To order valves manufactured according to your specific requirements, please contact our technical sales department.