
SY - 3 Way Ball Valve





The SY three-way ball valves are the professional's choice for hydraulic flow control. The valves are constructed with a common port at the base of the valve body. Any of the three peripheral ports can be connected to the common port - the other ports are totally sealed. SY is designed for three hydraulic control positions: Open, Closed, and Automatic.

- Passage size: SY3: 3.2 mm (1/8"), SY6: 6.0 mm (1/4")
 P.T.F.E. seals
 BSP or NPT threads
 Ball valve principle

- Using SY, the hydraulic valve can be manually opened/closed in case of operational fault
 Only one moving part
- Easy to assemble
- Easy viewing of the operating positionAll valves are sealed when in a 'between port' position
- Special large bore valve for controlling extra-large hydraulic valves (SY6)
 High quality Teflon seals and Chrome-Nickel plated balls, resistant to all types of
- irrigation water

1Y3A02000	1Y3A02100	SY-3	1/8" M	1/8" F	1/8" F	1/8" F	50
1Y3N02000	1Y3N02100	SY-3	1/8" F	1/8" F	1/8" F	1/8" F	50
1Y3A04000	1Y3A04100	SY-3	1/4" M	1/8" F	1/8" F	1/8" F	50
1Y3N04000	1Y3N04100	SY-3	1/4" F	1/8" F	1/8" F	1/8" F	50
1Y3N040A4	1Y3N041A4	SY-3	1/4" F	1/8" F	1/8" F	1/4" M	50
1Y3N040A2	1Y3N041A2	SY-3	1/4" F	1/8" M	1/8" F	1/8" F	50
1Y3N040A3	-	SY-3	1/4" F	1/8" F	1/8" M	1/8" M	50
1Y3A040A4	1Y3A041A4	SY-3	1/4" M	1/4" M	1/8" F	1/8" F	50
1Y6N04000	1Y6N04100	SY-6	1/4" F	1/4" F	1/4" F	1/4" F	25
1Y6A04000	1Y6A04100	SY-6	1/4" M	1/4" F	1/4" F	1/4" F	25