

3/4" BSPP Smart Tap Timer with Built-in Wi-Fi





Features

- Easy installation
- Connects directly to Wi-Fi 2.4 GHz, no hub required.
- App Control: Set and Check Irrigation Schedule from your smartphone or tablet from anywhere via the Tuya or Smart Life App
- Wi-Fi connection, Alexa, Google voice control, normal operation of device programs after disconnection
- Flexible programming
- Automatic irrigation. Can apply to drip irrigation systems, rain buckets, pet water and sprinkler irrigation etc.
- Lawn watering, potted drip irrigation, pool water storage, atomization cooling, temporary watering
- Build-in filter
- Normal Timing and Periodic Timing
- Anti-UV materials. Long term outdoor use, the product won't be deformed, aging, cracking.
- Low battery protector, cut-off the valve
- UV resistant material, long term outdoor use, the product won't be deformed, aging, cracking.
- Waterproof level IP55
- Manual rain delay is available in our water faucet timer to prevent over-watering and save much water in rain days, 1-7days.
- 4 Mode Operation
 - o Manual mode: Manually turn on off tap.
 - Normal Schedule: Unlimited Program to water for specified duration (1 min- 24 hrs)
 - Window / Cyle & Soak: Program a window to cycle On and OFF.
 - Countdown: Turn off the valve after the countdown expires (1 min- 24 hrs)
- Irrigation History, check when the tap timer was turned on and off.
- Watering Frequency: 1min -24, 1-7days (Mon Sun)
- Battery Indicator
- Assign to group, create a new group, or assign it to an existing group to control 2 valve or more valves together.
- Share: Give access to other people to control and monitor the valve





Technical Data

Port size	3/4" BSPP	Medium	Water
Maximum Working Pressure	0.8 MPa (8 bar)	Setting Method	App Control via Tuya or Smart Life App (iOS 10 and Android 5.0 above)
Minimum Working Pressure	0.05 MPa (0.5 bar)	Manual Override	Yes
Working voltage	DC 1.5V	IP Rating	IP55
Battery	4 x AA Alkaline Battery (not included)	_4 Mode Operation	 Manual mode: Manually turn on - off tap. Normal Schedule: Unlimited Program to water for specified duration (1 min- 24 hrs)
Standby Time	More than 3 months		
Rain Delay	Yes, 1 ∼ 7 days		 Window / Cyle & Soak: Program a window to cycle On and OFF. Countdown: Turn off the valve after the countdown expires (1 min- 24 hrs)
Colour	Green & Black	Working temperature	4.5°C∼45°C
Surface	Frosting	Dimensions	12cm x 11.5cm x 5cm

Packaging Includes:

- 1 x Tap Timer
- User Manual
- 1/2" BSPP Female to 3/4" Male Adapter
- 3/4" BSPP to 1/2" Barbed Fitting (Hose Connection Fitting)
- Teflon Tape



